

## Technical Specification:

	C7	C16
<b>Character Heights</b>	10/17 mm (0.39/0.66")	10/14/20/32 mm (0.39/0.55/0.78/1.26")
<b>Maximum Line Speed</b>	35 m/min (115 ft/min)	35 m/min (115 ft/min)
<b>Print Resolution</b>	Standard print	Standard print
<b>Ink Capacity</b>	1 or 3-Litre (2.11 or 6.34 US pints)	1 or 3-Litre (2.11 or 6.34 US pints)
<b>Print Head Length</b>	249 mm (9.80")	247 mm (9.72")
<b>Print Head Width</b>	112 mm (4.40")	112 mm (4.40")
<b>Print Head Depth</b>	88 mm (3.46")	108 mm (4.25")
<b>1-Litre Base</b>		
<b>Ink Base Height</b>	315.5mm (12.42")	315.5mm (12.42")
<b>Ink Base Width</b>	155 mm (6.10")	155 mm (6.10")
<b>Ink Base Depth</b>	110.5 mm (4.35")	110.5 mm (4.35")
<b>3-Litre Base</b>		
<b>Ink Base Height</b>	328.5 mm (12.93")	328.5 mm (12.93")
<b>Ink Base Width</b>	173mm (6.81")	173mm (6.81")
<b>Ink Base Depth</b>	110.5 mm (4.35")	110.5 mm (4.35")
<b>Unit Weight (200ml)</b>	N/A	N/A
<b>Unit Weight (1-Litre)</b>	8.2 Kg (18.07 lbs)	8.4 Kg (18.51 lbs)
<b>Unit Weight (3-Litre)</b>	11 Kg (24.25 lbs)	11.2 Kg (24.69 lbs)
<b>Construction</b>	Stainless steel	Stainless steel
<b>Electrical</b>	90 – 240 V @ 50 – 60 Hz	90 – 240 V @ 50 – 60 Hz
<b>Operating Temperature</b>	5° – 35° C (41° – 95° F)	5° – 35° C (41° – 95° F)
<b>Humidity (Non-condensing)</b>	10%-90%	10%-90%
<b>Options</b>	External photocell, Arabic characters	External photocell, Arabic characters