# PHYSICAL CHARACTERISTIC

Dimensions (HxWxD):

**Apex 2i:** 135 x 103 x 60 mm (5.1 x 4.1 x 2.4 in) **Apex 3i:** 156 x 127 x 58 mm (6.1 x 5.0 x 2.3 in) **Apex 4i:** 191 x 166 x 63 mm (7.5 x 6.5 x 2.5 in) **Weight:**\* 0.42 kg (14.7 oz); 0.52 kg (18.5 oz); 0.75 kg (26.5 oz)

**Weight:**\*\* 0.53 kg (18.7 oz); 0.75 kg (26.5 oz);

1.02 kg (36.1 oz)

Drop Specification: 1.2 m (4 ft)

\*With battery

\*\*With battery and paper roll

#### **USER ENVIRONMENT**

Operating Temperatures: -10°C to 50°C

(14°F to 122°F)

Storage Temperatures: -20°C to 60°C

(4°F to 140°F)

Charging temperatures: 5°C to 40°C

(41°F to 104°F)

Relative Humidity Range: 10% RH to 85% RH

non-condensing

ESD Protection: 8kV air gap, 4kV contact

## **PRINT TECHNOLOGY**

Printhead: Direct thermal, 8 dots per mm

(203 dots per in)

Print Mechanism Speed: 51 mm per second

(2 inches per second)

#### COMMUNICATION

Serial: RS232, up to 115.2 kbps USB: 2.0 (Apex 3 & 4 only) Bluetooth®: Version 2.1, Class 1

### MEDIA

Media Type: Direct thermal receipt paper (standard, premium, heavy duty, long-life, image protect, hi-temp, and all weather)
For optimum print quality and printer performance, use certified Honeywell media supplies.

#### AGENCY APPROVAL

Contact your Honeywell sales representative for the most recent list of agency approvals.

#### BARCODES/FONTS/GRAPHICS

Linear Symbologies: Codes 39, Code128 A/B/C, UCC/EAN-128, Interleaved 2 of 5, UPC/ EAN/JAN, Codabar, GS1 Databar, Code 93 2D Symbologies: PDF417, QR Code Optional Characters: Simplified & traditional Chinese, Hebrew, Arabic, Polish, Greek, Cyrillic, Thai, Vietnamese, Hangul (Korean)

**Graphics:** Supports 8-bit graphic printing, custom font, logo downloading

Standard Fonts: ASCII, international, PC line draw; 12CPI, 16CPI, 19CPI, 21CPI, 24CPI, 13CPI rotated

#### SOFTWARE/FIRMWARE

The Apex DO Toolkit Application (available from the Apple Store) includes:

Scan: Discover and pair/bond to Apex iOS

Bluetooth® printers.

Read and Display Printer Status: (characters in buffer, battery voltage, timer, temperature, print buffer remaining, firmware version, hardware version)

**Configure:** Font download, communications parameter set-up, printer custom attributes set-up, logo download

Presentation: Print demo receipts, forms,

logos, barcodes, and more Drivers: Windows, CE and desktop Form Fiesta Page Printing Utility Bootloader for Uploading Firmware

Info: General info about company and

application

**Software Development Kit:** Visual C++, Visual Basic; iOS, Android 2.2, 4.2, Blackberry®

#### **OPTIONS**

Android 2.2 to 4.2 Bluetooth® Version 2.1 Integrated Magnetic Stripe Card Reader iOS Bluetooth® Version 2.1 iOS 5, iOS 6 & iOS 7 IrDA: IrLPT v1.0; IrCOMM v1.0

#### WARRANTY

Standard Warranty:

Printer: 1 year\*

**Printhead:** 1 year\* or 25,400,000 mm (1,000,000 in),

whichever comes first)

**Extended Warranty:** Contact your Honeywell sales representative for extended warranty options available through Honeywell Repair Services

\* Covers platen roller, printhead and installed options

